

# RIFLE THREAT PERFORMANCE MATRIX



## BALLISTIC INSERTS

SERIES	MODEL	RATING	WEIGHT	THICKNESS	LEAD CORE				MILD STEEL CORE				ARMOR PIERCING CORE				ENHANCED PERFORMANCE						
					5.56 x 45 mm - M193 Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M67 Max Velocity 2390 ft/s (728 m/s)	7.62 x 51 mm - M80 Max Velocity 2800 ft/s (853 m/s)	7.62 x 63 mm - JSP Max Velocity 2780 ft/s (847 m/s)	5.56 x 45 mm - M855/SS109 Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M43 Max Velocity 2390 ft/s (728 m/s)	7.62 x 54R - LPS Max Velocity 2850 ft/s (869 m/s)	7.62 x 39 mm - AP1 Max Velocity 2390 ft/s (728 m/s)	7.62 x 54R B-32 - AP1 Max Velocity 2850 ft/s (869 m/s)	7.62 x 51 mm - M61 Max Velocity 2900 ft/s (884 m/s)	7.62 x 63 mm - AP M2 Max Velocity 2900 ft/s (884 m/s)	5.56 x 45 mm - M855A1 Max Velocity 3050 ft/s (930 m/s)	7.62 x 51 mm - M80A1 Max Velocity 3050 ft/s (930 m/s)	SH	LE	SA	SW		
800	3800*	NIJ Level III	2.2 lb / 1.0 kg	1.05 in / 27 mm	■	■	■	■	■											■	■	■	■
	3800C*	NIJ Level III	2.4 lb / 1.1 kg	0.95 in / 24 mm	■	■	■		■													■	■
	3800LV	NIJ Level III (ICW)	2.1 lb / 1.0 kg	0.55 in / 14 mm	■	■	■	■	■													■	■
	3810*	NIJ Level III+	3.9 lb / 1.8 kg	0.98 in / 25 mm	■	■	■	■	■	■												■	■
	3810B	NIJ Level III+	4.1 lb / 1.9 kg	1.12 in / 28 mm	■	■	■	■	■	■												■	■
	3810LV	NIJ Level III+ (ICW)	3.9 lb / 1.7 kg	0.60 in / 15 mm	■	■	■	■	■	■												■	■
	4800	NIJ Level IV	4.9 lb / 2.2 kg	1.04 in / 26 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
	4800LV	Special Rifle Threats	4.7 lb / 2.1 kg	0.67 in / 17 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
	4800LVC	Special Rifle Threats	4.9 lb / 2.3 kg	0.71 in / 18 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
600	3611C*	NIJ Level III+	3.9 lb / 1.8 kg	1.05 in / 27 mm	■	■	■		■	■											■	■	
	4601*	NIJ Level IV	6.4 lb / 2.9 kg	1.18 in / 30 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
400	3403	NIJ Level III	3.3 lb / 1.5 kg	1.06 in / 27 mm	■	■	■	■	■													■	■
	3411	NIJ Level IV	6.2 lb / 2.8 kg	1.13 in / 29 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
	4402	NIJ Level IV	7.5 lb / 3.4 kg	0.85 in / 22 mm	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■
200	L210	Special Rifle Threats	5.5 lb / 2.5 kg	0.59 in / 15 mm	■	■			■	■			■								■		
	M210	Special Rifle Threats	5.1 lb / 2.3 kg	0.61 in / 15 mm	■	■			■	■			■								■	■	
	U210	Special Rifle Threats	3.9 lb / 1.8 kg	0.56 in / 14 mm	■	■			■	■			■								■	■	
	D220**	DEA Special Threats	5.7 lb / 2.6 kg	0.68 in / 17 mm			■		■	■												■	■

\* NIJ Certified / CPL Listed

\*\* Additional D220 DEA-specified threats tested:

■ .223 Remington Bonded Soft Pt, 62 gr @ 2620 ± 50 fps ■ .308 Winchester PSPB, 150 gr @ 2600 ± 50 fps. See D220 Tech Sheet for more information about DEA-specified threats and testing protocol.

Weights listed are based on SH or SW, size L. All torso plates—with the exception of L210—are Multi Curve.

For information about model P210 (hand gun protection) and 100 SERIES Trauma and Side plates, please go to [hesco.com](http://hesco.com) or contact your Hesco Armor representative.

Hesco Armor 2210 Port Industrial Road · Aberdeen, Washington 98520 · United States · +1 360 637 6867 · support@hesco.com

STOP EVERYTHING. | [hesco.com](http://hesco.com)

Information contained in this document is intended solely to provide general guidance. The right is reserved to make changes to this document without notice at any time. Nothing in this document (i) constitutes an offer, representation, warranty, term or condition or (ii) is a substitute for the need to employ adequate independent technical expertise and judgment. **Patents and Trademarks:** HESCO® products are subject to patents and/or patent applications in territories around the world. HESCO® is a registered trademark of Hesco Bastion Ltd and its affiliates ("Hesco") around the world. Other trademarks also apply. For full details, please go to: [www.hesco.com/legal\\_notice](http://www.hesco.com/legal_notice) **Quality Standards:** Hesco operates a Quality Management System certified to ISO 9001:2015/BA 9000:2016, Approved Certificate number: C2019-01385. AQAP 2110 Conformance, Approved Certificate Number: C2019-01645. This material is subject to copyright protection. Copyright © 2021 Hesco. All rights reserved.