



MODEL T212



BALLISTIC INSERT

THICKNESS: 0.54 in (17 mm), AREAL DENSITY: 6.71 lb/ft²

SHOOTER CUT - SINGLE CURVE - TORSO PLATES

PART NUMBER	WIDTH x LENGTH	WEIGHT
T212-SH-SC-L	10.00 x 12.00 in (254 x 305 mm)	4.7 lb (2.1 kg)

Manufacturing Tolerances:

Thickness dimensions are $\pm 1/8$ in (± 3 mm). Width and length dimensions are +0.00 to -0.25 in (0.00 to -6mm). All weights are $\pm 5\%$.

THREAT PERFORMANCE MATRIX: T212

	LEAD CORE		MILD STEEL CORE		ENHANCED PERF
	5.56 x 45 mm - M193 Max Velocity 3280 ft/s (1000 m/s)	7.62 x 39 mm - M67 Max Velocity 2410 ft/s (735 m/s)	5.56 x 45 mm - M855/SS109 Max Velocity 3150 ft/s (960 m/s)	7.62 x 39 mm - M43 Max Velocity 2410 ft/s (735 m/s)	5.56 x 45 mm - M855A1 Max Velocity 3180 ft/s (969 m/s)
T212-SH-SC-L	3	3	3	2	3

Hesco Testing Protocol

NIJ Certification of hard armor requires submission of 10" x 12" test plates which must demonstrate the ability to defeat specific rounds tested to a valid NIJ shot pattern, after exposure to a stringent conditioning protocol to simulate aging and wear.

Hesco holds itself to a higher standard by publishing the minimum number of shots that each size plate can be expected to defeat under similar NIJ testing methods, as well as listing many additional threats not addressed under NIJ Certification process. The minimum number of shots are shown in the Threat Performance Matrix.

General Information

Ceramic/composite design. Light AP protection including 7.62 x 39 API. Multi shot rated on selected threats. Water repellent polyurethane coated 1000 Denier CORDURA® fabric finish. Made in the U.S.A.

NIJ Standard-0101.06

Special threat testing conducted in accordance with NIJ Standard-0101.06 (modified).

Disclaimer

The information contained in this document is intended solely to provide general guidance. The right is reserved to make changes to this document without notice at any time. Nothing in this document (i) constitutes an offer, representation, warranty, term or condition or (ii) is a substitute for the need to employ adequate independent technical expertise and judgment.

